

Frame Tank Installation Instructions

The following shows typical setup and installation instructions for the folding frame tank. When setting up this tank, please make sure that the placement area is flat (not a slope) and free from stones, roots, or other sharp objects.

Step 1: Prepare the ground for tank placement by leveling the ground and clearing away all rocks, sharp stones, glass or other potentially harmful items.

Step 2 (Recommended): Lay out a berm liner or ground cloth (if applicable) in intended storage area. Berm should be flat and ready for the placement of the tank. If berm or liner is not being used, a sand layer can also be placed on the ground if needed for added support.

Step 3: Unfold the tank. Ensure that the tank liner is not pinched or impeded by the frame.

Note: If this is the first assembly please see the [Frame Tank Setup Page](#) for initial setup.

Step 4: Prepare your tank to be filled by checking that the discharge valves, drains and other fittings are closed. Verify that there are no products or equipment that will get in the way of the tank as it is being filled.

Emptying the Tank: To empty your tank, connect discharge hoses to the discharge ports. When connected, open the gate or ball valve. Opening the vent is not required to discharge the liquid. A pump can speed up the discharge if necessary.



Note: A pipe thread sealant is recommended for all flexible tank fittings. This ensures there is no leakage. The sealant used should be compatible with the tank's contents. Sealant is not included.

Frame Tank Frame Setup

Step 1: Unfold the frame sections.

Step 2: Slide the male connector in the receiving end and fasten with screws provided.

Step 2: Unroll or unfold the tank and orient inside the frame.

Step 3: Lace the rope through the grommets and around the frame.

